



# HUSKY™ ABRASION-RESISTANT Air-Operated Double-Diaphragm Pumps



1 inch (25.4 mm)  
Husky 1040

1-1/2 inch (38.1 mm)  
Husky 1590

2 inch (50.8 mm)  
Husky 2150

3 inch (76.2 mm)  
Husky 3275

## A Full Line of Rugged New Pumps Designed for the Toughest Applications


### Features and Benefits

- Quality air valve with closed-center design eliminates sticking commonly experienced with spool-valve designs
- Full line of abrasion-resistant aluminum pumps in 1 in (25.4 mm), 1-1/2 in (38.1 mm), 2 in (50.8 mm) and 3 in (76.2 mm) sizes
- 1 in (25.4 mm) through 2 in (50.8 mm) pumps use common center section to reduce inventory
- Significant increase in pump life: 2 to 3 times longer than the previous ball check design and clearly outperforms the competition
- 2 in (50.8 mm) pump matches the inlet to outlet dimensions of Wilden® and Aro® aluminum pumps for ease of installation in existing applications

# ABRASION-RESISTANT

For further information, contact your local Graco Distributor.

## Improved Ball Guide Design For Longer Life!



Manifold

90° ball stop increases ball guide life which extends pump performance in tough applications.



Fluid Cover

## Ordering Information

Part No. (npt)	Part No. (bsp)	Size	Seat	Ball	Diaphragm
D73525	D7C525	1 in (25.4 mm)	Hytrel	Acetal	Hytrel
D73GGG	D7CGGG	1 in (25.4 mm)	Geolast	Geolast	Geolast
D733GG	D7C3GG	1 in (25.4 mm)	Stainless Steel	Geolast	Geolast
DB3525	DBC525	1.5 in (38.1 mm)	Hytrel	Acetal	Hytrel
DB3GGG	DBC3GGG	1.5 in (38.1 mm)	Geolast	Geolast	Geolast
DB33GG	DBC3GG	1.5 in (38.1 mm)	Stainless Steel	Geolast	Geolast
DF3525	DFC525	2 in (50.8 mm)	Hytrel	Acetal	Hytrel
DF3GGG	DFCGGG	2 in (50.8 mm)	Geolast	Geolast	Geolast
DF33GG	DFC3GG	2 in (50.8 mm)	Stainless Steel	Geolast	Geolast
DK3525	DKC525	3 in (76.2 mm)	Hytrel	Acetal	Hytrel
DK3GGG	DKCGGG	3 in (76.2 mm)	Geolast	Geolast	Geolast
DK33GG	DKC3GG	3 in (76.2 mm)	Stainless Steel	Geolast	Geolast

**Hytrel:** Excellent abrasion resistance for non-solvent-based material.

**Acetal:** Excellent fatigue and abrasion resistance for solvent-based materials.

**Geolast:** Same chemical compatibility as Hytrel with greater abrasion resistance.

**Stainless Steel:** Greatest chemical compatibility and abrasion resistance.

## Husky 2150 2 in (50.8 mm) Pump Comparison

	Graco	Major Competitors
Inlet/Outlet Distance	22.875 in (58.1 cm)	22.875 in (58.1 cm)

### Husky 2150 Extended Pumps

Part No. (npt)	Part No. (bsp)	Size	Seat	Ball	Diaphragm
DFH525	DFG525	2 in (50.8 mm)	Hytrel	Acetal	Hytrel
DFHGGG	DFGGGG	2 in (50.8 mm)	Geolast	Geolast	Geolast
DFH3GG	DFG3GG	2 in (50.8 mm)	Stainless Steel	Geolast	Geolast
234019	Retrofit kit for increasing the height of current Graco 2150 Aluminum pump				



2 inch (50.8 mm)  
Husky 2150 Extended

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. Graco Inc. is registered to I.S. EN ISO 9001.



GRACO N.V.  
Industrieterrein Oude Bunders  
Slakweidestraat 31 • B-3630 Maasmechelen  
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777  
www.graco.be

©2002 Graco Inc. Form No. 320-469 E (Rev.A) 5/02 Printed in Europe.

All brand names or marks are used for identification purposes and are trademarks of their respective owners.